



- NOTE: 1. THE COLOR BATCH TEST REPORT IS ONLY FOR FIRST LOT TEST.
 色母環保檢測報告, 僅提供原始測試報告.
 2. VOLTAGE: 5kV, $\leq 10\text{mA}$, 10 SECONDS.
 耐電壓測試: 5kV $\leq 10\text{mA}$, 10秒.
 3. MADE OF EQUIVALENT MATERIAL.
 可使用同等材質.



康揚企業股份有限公司
 KANG YANG HARDWARE ENTERPRISE CO., LTD.
 康揚塑膠(東莞)有限公司
 KANG YANG PLASTIC(DONG GUAN)CO.,LTD.
 康哲電腦配件(吳江)有限公司
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE	TITLE	DWG. NO.	PART NO.
	2015.03.24	THREADED SPACER	MTPD632-11.9V0BNLR	MTPD632-11.9V0BNLR
	DRAWN	MATERIAL	SIZE	SPEC. DWG.
	ROBERT	NYLON 66 UL94V-0	A4	REV
CHECKED	COLOR	FINISH	A	A
林祺翔	BLACK			
APPROVED	UNLESS OTHERWISE SPECIFIED		SCALE: 4:1	UNIT mm
Kang	TOLERANCE: SEE ABOVE			SHEET 1 OF 1