







PART NO.	TORQUE
DP007A(25)	25±15 gf/cm
DP007A(50)	50±15 gf/cm
DP007A(80)	80±20 gf/cm
DP007A(100)	100±20 gf/cm
DP007A(120)	120±20 gf/cm
DP007A(150)	150±20 gf/cm



- NOTE: 1. MODULUS(模數): 0.8
 2. PITCH DIAMETER(節圓直徑): $\phi 10.4$
 3. NUMBER OF TEETH(齒數): 13
 4. PRESSURE ANGLE(壓力角): 20°
 5. TORQUE(扭力): SEE ABOVE
 6. PLACE IN ROOM TEMPERATURE, THE TORQUE AT 20rpm/min SHALL BE WITHIN UPPER TABLE.
 標準室溫底下, 20轉/分鐘 扭力須符合上表.
 7. SPECIAL COMMENTS(特別條件)
 7-1 "ROOM TEMPERATURE" IN THIS DRAWING MEANS THE SAME DEFINED.
 (TEMPERATURE: $23 \pm 2^\circ \text{C}$, RELATIVE HUMIDITY: $50 \pm 10\%$)
 圖面上指的室溫為 $23 \pm 2^\circ \text{C}$, 濕度 $50 \pm 10\%$
 7-2 TORQUE WILL BE CHANGED BY TEMPERATURE AND RPM.
 扭力會隨溫度及轉速而有所差異.
 8. MADE OF EQUIVALENT MATERIAL.
 均可使用同等材質

REVISIONS			
REV	DESCRIPTION	DATE	BY

 康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.				TITLE		SPEC. DWG.	
				BODY MATERIAL		DATE	
				ABS UL94HB		2005.04.08	
				GEAR MATERIAL		DRAWN	
				POM UL94HB		James	
PART NUMBER		DRAWING NUMBER		COLOR		CHECK	
SEE ABOVE		DP007A		BLACK		Kenny	
SIZE	SCALE	UNIT	REV	UNLESS OTHERWISE SPECIFIED TOLERANCE		APPROVED	
A4	2.5:1	mm	A	SEE ABOVE		Kana	