






MOUNTING HOLE

NOTE: 1. THE BEST USE TIME FOR NICKEL PLATED PARTS ARE WITHIN 6 MONTHS SINCE MFG DATE.
 鍍鎳最佳使用時間, 為製造日起6個月內。
 2. FINISH: NICKEL PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.
 表面為鍍鎳, 未使用完畢時, 產品請密封。



康揚企業股份有限公司
 KANG YANG HARDWARE ENTERPRISE CO., LTD.
 康揚塑膠(東莞)有限公司
 KANG YANG PLASTIC(DONG GUAN)CO., LTD.
 康哲電腦配件(吳江)有限公司
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN
 THIS DRAWING IS THE SOLE PROPERTY
 OF KANG YANG HARDWARE
 ENTERPRISE CO. ANY
 REPRODUCTION IN PART OR AS A
 WHOLE WITHOUT THE WRITTEN
 PERMISSION OF
 KANG YANG HARDWARE ENTERPRISE
 CO. IS PROHIBITED.

DO NOT SCALE DRAWING

DATE
2008.02.13

DRAWN
leeya

CHECKED
林祺翔

APPROVED
Kang

TITLE
GROUND TERMINAL

MATERIAL
BRASS

FINISH
NI PLATED

UNLESS OTHERWISE SPECIFIED
 TOLERANCE: SEE ABOVE

DWG. NO.
GND-37

PART NO.
GND-37

SIZE
A4

SPEC. DWG.

REV
C

SCALE: 3:1

UNIT
mm

SHEET 1 OF 1