




MOUNTING HOLE

NOTE: 1. THE BEST USE TIME FOR NICKEL PLATED PARTS ARE WITHIN 6 MONTHS SINCE MFG DATE.

鍍鎳最佳使用時間，為製造日起6個月內。

2. FINISH: NICKEL PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.

表面為鍍鎳，未使用完畢時，產品請密封。

3. SUGGEST RATED CURRENT: 15A.

建議額定電流：15A。



康揚企業股份有限公司
KANG YANG HARDWARE ENTERPRISE CO., LTD.
康揚塑膠(東莞)有限公司
KANG YANG PLASTIC(DONG GUAN)CO., LTD.
康哲電腦配件(吳江)有限公司
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED.	DATE	2001.09.07	TITLE	P.C.B TERMINAL	DWG. NO.	PC250-4	PART NO.	PC250-4
	DRAWN	AMY	MATERIAL	BRASS	SIZE	A4	SPEC. DWG.	REV
	CHECKED	林祺翔	COLOR	FINISH				A
	APPROVED	康揚	UNLESS OTHERWISE SPECIFIED TOLERANCE: SEE ABOVE		SCALE: 3:1	UNIT	mm	SHEET 1 OF 1