








MOUNTING HOLE

PART NO.	THREAD	MARK
PCB-8	M3X0.5P	M3
PCB-8(M4)	M4X0.7P	M4
PCB-8(632)	#6-32	632

NOTE:1. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.

鍍錫最佳使用時間, 為製造日起3個月內.

2. FINSH : TIN PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.

表面為鍍錫, 未使用完畢時, 產品請密封.

3. SUGGEST RATED CURRENT: 20A.

建議額定電流: 20A.



康揚企業股份有限公司
KANG YANG HARDWARE ENTERPRISE CO., LTD.
康揚塑膠(東莞)有限公司
KANG YANG PLASTIC(DONG GUAN)CO., LTD.
康哲電腦配件(吳江)有限公司
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED.	DATE 2001.03.23	TITLE P.C.B TERMINAL	DWG. NO. PCB-8		PART NO. SEE ABOVE	
	DRAWN JASON	MATERIAL BRASS				
	CHECKED 彭永成	COLOR FINISH TIN PLATED	SIZE A4	SPEC. DWG.	REV C	
	APPROVED Kang	UNLESS OTHERWISE SPECIFIED TOLERANCE: SEE ABOVE	SCALE: 3:1	UNIT mm	SHEET 1 OF 1	

DO NOT SCALE DRAWING