





COMBINATION ILLUSTRATION DWG
(MOUNTING HOLE)

NOTE: 1. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.

鍍錫最佳使用時間，為製造日起3個月內。

2. FINISH: TIN PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.

表面為鍍錫，未使用完畢時，產品請密封。



康揚企業股份有限公司
KANG YANG HARDWARE ENTERPRISE CO., LTD.
康揚塑膠(東莞)有限公司
KANG YANG PLASTIC(DONG GUAN)CO., LTD.
康哲電腦配件(吳江)有限公司
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN
THIS DRAWING IS THE SOLE PROPERTY
OF KANG YANG HARDWARE
ENTERPRISE CO. ANY
REPRODUCTION IN PART OR AS A
WHOLE WITHOUT THE WRITTEN
PERMISSION OF
KANG YANG HARDWARE ENTERPRISE
CO. IS PROHIBITED.

DO NOT SCALE DRAWING

DATE
2013.06.19
DRAWN
ROBERT
CHECKED
李柏甯
APPROVED
Kang

TITLE
P.C.B TERMINAL
MATERIAL
BRASS
COLOR
FINISH
TIN PLATED
UNLESS OTHERWISE SPECIFIED
TOLERANCE:
SEE ABOVE

DWG. NO.
PCLTM-250

PART NO.
PCLTM-250

SIZE
A4

SPEC. DWG

REV
A

SCALE: 3:1

UNIT
mm

SHEET 1 OF 1