

DIM.	TOL
L≤10	±0.2
10 <l≤30< td=""><td>±0,3</td></l≤30<>	±0,3
30 <l≤50< td=""><td>±0.5</td></l≤50<>	±0.5
50 <l≤100< td=""><td>±0.7</td></l≤100<>	±0.7
100 <l≤250< td=""><td>±1.2</td></l≤250<>	±1.2
ABOVE 250	±1.5

REVISIONS					
REV	DESCRIPTION	DATE	BY		





PART NO.	COLOR	DOUBLE ADHESIVE TAPE	
FCA-11		THICKNESS=1.1mm	
FCA-11(3M)	NATURAL	THICKNESS=0.9mm	
FCA-11B BLACK THICK		THICKNESS=1.1mm	
FCA-11(B)3M	DLACK	THICKNESS=0.9mm	

NOTE:1. The height is not included thickness of adhesive tape and separate paper

- 2. The adhesive tape is cut by hand , it is normal if there is a not unified edge.
- 3. All measurement does not include gate which raises under 0.3mm.
- 4. The reduced is normal.

康揚企業股份有限公司	WIRE MOUNT	SPEC. DWG.
RANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 ISO 8001 KANG YANG PLASTIC(DONG GUAN)CO.,LTD.	MATERIAL NYLON 66 UL94V—2	DATE 2012.11.30
150 9001 KANG YANG PLASTICIDONG GUAN 1CO.,LTD. 150 160000 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO.,LTD.	HARDNESS	ROBERT
PART NUMBER SEE ABOVE FCA-11	COLOR SEE ABOVE	CHECK 具蓋重 (又京)
SIZE SCALE 3:2 UNIT MM REV C	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	APPROVED Kong