
DIM.	TOL
5mm DOWN	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm UP	+1.0

		REVISIONS	
BY	DATE	DESCRIPTION	REV D





PART NO.	DOUBLE ADHESIVE TAPE	COLOR	Α	В	С	D	
FCA-5	3M THICKNESS=1.1mm	NIATLIDAL	NIATUDAL				
FCA-5(3M)	3M THICKNESS=0.9mm	NATURAL	19.8	45.4	31.8	15.2	
FCA-5(B)	3M THICKNESS=1.1mm	BLACK					

NOTE: 1. THE PRODUCT SIZE IS NOT INCLUDED THE SIZES OF ADHESIVE TAPE AND ITS LINER. 產品尺寸皆不含背膠及離型紙.

- 2. IT IS HAND-CUT ADHESIVE TAPE, SO CAN NOT PERFECTLY STICK EVENLY. IT IS POSSIBLE TO HAVE SOME PORTION EXPOSED OR SHIRNKING INWARD. THIS IS A NORMAL PHENOMENON. 此為手工背膠,貼附無法非常平整,會有外露或內縮屬正常現象.
- 3. SHRINKING IS NORMAL STATUS. 內縮為正常現象.
- 4. MADE OF EQUIVALENT MATERIAL. 均可使用同等材質.

康揚企業股		WIRE MOUNT	SPEC. DWG.
RANG YANG HARDWARE ENTERPRISE CO., LTD.  康揚塑膠(東莞)有限公司  ISO 9001 KANG YANG PLASTICIDONG CUAN JCO.,LTD. ISO 14001 東哲電腦配件(吳江)有限公司  RANG CHE COMPUTER COMPONENTS(WUJIANG) CO.,LTD.		NYLON 66 UL94V—2	2005.10.12
		FINISH	drawn Syman
PART NUMBER SEE ABOVE	DRAWING NUMBER FCA-5	SEE ABOVE	CHECK
SIZE A4 SCALE 1:1	unit mm rev C	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	APPROVED