





DIM.	TOL
L≤10	±0.2
10<L≤30	±0.3
30<L≤50	±0.5
50<L≤100	±0.7
100<L≤250	±1.2
ABOVE 250	±1.5

REVISIONS			
REV	DESCRIPTION	DATE	BY



DOUBLE ADHESIVE TAPE

NOTE: The Height is not including the thickness of release paper

QMFZ2 Component - Plastics Wednesday
 E I DUPONT DE NEMOURS & CO INC
 ENGINEERING POLYMERS CHESTNUT RUN PLAZA PO BOX 80713 WILMINGTON DE 19880
 Material Designation: 101(+)(f1), 101F(+)(f1), 101L(+)(f1), B101(+)(f1), B101L(f1), 132F(+)(f1), 135F(+)(f1)
 Product Description: Polyamide 66 (PA66), designated "Zytel" furnished as pellets.

B41934

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC	IEC GWFI
ALL	0.71	V-2	4	0	130	75	85	GWIT	960
	1.5	V-2	3	0	130	75	85	725	960
	3	V-2	2	0	130	75	85	800	960
	6	V-2	2	0	130	75	85	800	960

CTI: 0 HVTR: 0 D495: 6 IEC Ball Pressure (°C): -
 Strength (kV/mm): 13 Volume Resistivity (10¹⁰ ohm-cm): 14 Dimensional Stability(%) -
 ISO Tensile Strength (MPa): ISO Flexural Strength (MPa): - ISO Heat Deflection (°C):
 ISO Tensile Impact (kJ/m²): ISO Charpy Impact (kJ/m²): -
 ISO Izod Impact (kJ/m²): -
 (+) Virgin and regrind up to 50% by weight inclusive, have the same basic material characteristics.
 (f1) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.
 NOTE (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" or "MIN" or "ZEN" or "DEL" or "CRA" or "RYN".
 Report Date: 7/29/1996 Underwriters Laboratories Inc®
 UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined.

 康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.				TITLE		SPEC. DWG.	
				WIRE MOUNT		DATE	
				MATERIAL		2010.05.21	
				NYLON 66 UL94V-2		DRAWN	
PART NUMBER				FINISH		JIM	
FWAS-4(G)				COLOR		CHECK	
DRAWING NUMBER				GRAY		陳彥璋	
FWAS-4				UNLESS OTHERWISE SPECIFIED TOLERANCE		APPROVED	
SIZE				A4		SEE ABOVE	
SCALE				1:2		Kang	
UNIT				mm			
REV				A			