


DIM.	TOL.
X	±0.3
X.X	±0.2
X.XX	±0.1

REVISIONS			
REV	DESCRIPTION	DATE	BY



Component - Plastics

E41938

E I DUPONT DE NEMOURS & CO INC
ENGINEERING POLYMERS, CHESTNUT RUN PLAZA, PO BOX 80713, WILMINGTON DE 19880
101(r9)(f1), 101F(r9)(f1), 101L(r9)(f1), E101(r9)(f1), E101L(r9)(f1)
Polyamide 66 (PA66), "Zytel", furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	0.75	V-2	4	0	130	75	85
	1.5	V-2	3	0	130	75	85
	3.0	V-2	2	0	130	75	85
	6.0	V-2	2	0	130	75	85

Comparative Tracking Index (CTI): 0
Dielectric Strength (kV/mm): 13
High-Voltage Arc Tracking Rate (HATR): 0
Dimensional Stability (%): -
Inclined Plane Tracking (IPT): -
Volume Resistivity (10¹⁴ ohm-cm): 14
High-Volt, Low Current Arc Resis (P499): 6

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

NOTE - (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" for Zytel or "MIN" for Minlon or "DEL" for Delrin or "GRA" for Grastin or "RYN" for Rynite or "ETPV" for ETPV grades.

19 - Virgin and reground up to 25% by weight inclusive, have the same basic material characteristics for ALL colors down to 0.75mm. For thicknesses 0.40mm to 0.70mm the same basic material characteristics exist with the exception of generic RTI for all proper/ups and Regrind exceeding 25% is limited to V-2 Flammability for WT, RD, BK.

ANSIUL 94 semi-scale test data does not pertain to building materials, furnishings and related contents. ANSIUL 94 semi-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1009-07-20
Last Revised: 2010-07-27

© 2011 Underwriters Laboratories Inc.



 康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.				TITLE LED SPACER SUPPORT		SPEC. DWG.	
				MATERIAL NYLON 66 UL94V-2 or EQUIVALENT		DATE 2013.08.28	
PART NUMBER LED-1.5L				FINISH		DRAWN ALBERT	
DRAWING NUMBER LED-1.5L				COLOR NATURAL		CHECK 	
SIZE A4		SCALE 4:1		UNIT mm		APPROVED Kang	
LED-1.5L		LED-1.5L		UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE			