





MOUNTING HOLE $\phi 5.2^{+0.1}_{-0}$
THICKNESS 0.8~1.0

- NOTE: 1. SUITABLE FOR $\phi 3$ LED WITH VISOR AND 2PIN.
適用於 $\phi 3$ LED有帽緣的, 適用於2PIN.
2. THE COLOR BATCH TEST REPORT IS ONLY FOR FIRST LOT TEST.
色母環保檢測報告, 僅提供原始測試報告.
3. SHRINKING IS NORMAL STATUS.
內縮屬正常現象.
4. MADE OF EQUIVALENT MATERIAL.
可使用同等材質.



康揚企業股份有限公司
KANG YANG HARDWARE ENTERPRISE CO., LTD.
康揚塑膠(東莞)有限公司
KANG YANG PLASTIC(DONG GUAN)CO., LTD.
康哲電腦配件(吳江)有限公司
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE 2009.03.16	TITLE LED HOLDER	DWG. NO. LED3-17		PART NO. LED3-17(B)	
	DRAWN SAI	MATERIAL NYLON 66 UL94V-2				
	CHECKED 林祺翔	COLOR BLACK	FINISH	SIZE A4	SPEC. DWG.	REV A
	APPROVED Kang	UNLESS OTHERWISE SPECIFIED TOLERANCE: SEE ABOVE		SCALE: 6:1	UNIT mm	SHEET 1 OF 1