




成型尺寸	公差
5mm以下	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm以上	±1.0

REVISIONS			
REV	DESCRIPTION	DATE	BY

專利品



A: HOLE IN CHASSIS: $\phi 7.5^{+0.1}_{-0}$
CHASSIS THICKNESS: 1.0~1.5mm

註: 產品適用2 PIN, $\phi 5$ 有帽緣的LED燈裝配.

QMF22 Component - Plastics Wednesday

E I DUPONT DE NEMOURS & CO INC
ENGINEERING POLYMERS CHESTNUT RUN PLAZA PO BOX 80713 WILMINGTON DE 19880
Material Designation: 101(+)(f1), 101P(+)(f1), 101L(+)(f1), E101(+)(f1), E101L(f1), 132P(+)(f1), 135P(+)(f1)
Product Description: Polyamide 66 (PA66), designated "Zytel" furnished as pellets.

E41938

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	0.71	V-2	4	0	130	75	85	725	960
	1.5	V-2	3	0	130	75	85	750	960
	3	V-2	2	0	130	75	85	800	960
	6	V-2	2	0	130	75	85	800	960

CTE: 0

HVTR: 0

D495: 6

IEC Ball Pressure (C):
Dimensional Stability (%):
ISO Heat Deflection (C):
ISO Charpy Impact (kJ/m²):

Strength (N/mm²):
ISO Tensile Strength (N/mm²):
ISO Tensile Impact (kJ/m²):

Volume Resistivity (10¹⁰ ohm-cm): 14

ISO Flexural Strength (N/mm²):

ISO Load Impact (kJ/m²):

(+) Virgin and regird up to 50% by weight inclusive, have the same basic material characteristics.

(f1) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

NOTE (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" or "MIN" or "ZEN" or "DEL" or "CRA" or "RYN".

Report Date: 7/29/1996 Underwriters Laboratories Inc®
UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by the user.

 康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.				TITLE LED間隔柱		產品規格圖面	
PART NUMBER LED5-18L(B)				MATERIAL NYLON 66 UL94V-2		DATE 2012.01.12	
DRAWING NUMBER LED5-18L(B)				HARDNESS		DRAWN SAI	
SIZE A4				COLOR BLACK		CHECK 	
SCALE 3:1				UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE		APPROVED 	
UNIT mm				REV A			