


DIM.	TOL.
5mm DOWN	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm UP	±1.0

Patented Product
專利產品

REVISIONS			
REV	DESCRIPTION	DATE	BY



A: HOLE IN CHASSIS: $\phi 7.5^{+0.1}_{-0}$
CHASSIS THICKNESS: 0.6~1.2

NOTE: 1. All measurement does not include gate which raises under 0.3mm.
2. Suitable for $\phi 5$ LED with visor and 2PIN.

Component - Plastic

E41938

E I DUPONT DE NEMOURS & CO INC
ENGINEERING POLYMERS, CHESTNUT RUN PLAZA, PO BOX 80713, WILMINGTON DE 19880
101(r9)(f1), 101F(r9)(f1), 101L(r9)(f1), E101(r9)(f1), E101L(r9)(f1)
Polyamide 66 (PA66), "Zytel", furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HA1	RT1 Elec	RT1 Imp	RT1 Str
ALL	0.71	V-2	4	0	130	76	85
	1.5	V-2	3	0	130	75	85
	3.0	V-2	2	0	130	76	85
	6.0	V-2	2	0	130	75	85

Comparative Tracking Index (CTI): 0
Dielectric Strength (kV/mm): 13

High-Voltage Arc Tracking Rate (HVTR): 0
Dimensional Stability (%): -

Inclined Plane Tracking (IPT): -
Volume Resistivity (10^9 ohm-cm): 14
High Volt, Low Current Arc Tests (DAB): 6

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 745C.

NOTE: (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" for Zytel or "MIN" for Minlon or "DEL" for Delrin or "CRA" for Crastin or "RYN" for Rynite or "ETPV" for ETPV grades.

r9 - Virgin and regrid up to 50% by weight inclusive, have the same basic material characteristics for ALL colors down to 0.71mm. For thickness 0.40mm to 0.70mm the same basic material characteristics exist with the exception of generic RT1s for all properties and Regrid exceeding 25% is limited to V-2 Flammability for WT, RD, BK.


ANSI/UL 84 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 84 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1993-07-29
Last Revised: 2010-07-27

© 2011 Underwriters Laboratories Inc.

UL US

NYLON 66 UL94V-2 or EQUIVALENT

 康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.				TITLE LED HOLDER		SPEC. DWG.	
				MATERIAL NYLON 66 UL94V-2		DATE 2008.12.19	
				HARDNESS		DRAWN SAI	
				COLOR BLACK		CHECK 	
PART NUMBER LED5-18M(B)		DRAWING NUMBER LED5-18M(B)		UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE		APPROVED 	
SIZE A4	SCALE 3:1	UNIT mm	REV B				