



成型尺寸	公差
5mm以下	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm以上	±1.0

REVISIONS			
REV	DESCRIPTION	DATE	BY



Component - Plastic

E41938

E I DUPONT DE NEMOURS & CO INC
ENGINEERING POLYMERS, CHESTNUT RUN PLAZA, PO BOX 80713, WILMINGTON DE 19880

101(r9)(f1), 101F(r9)(f1), 101L(r9)(f1), E101(r9)(f1), E101L(r9)(f1)
Polyamide 66 (PA66), "Zytel", furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HAZ	RTI Elec	RTI Imp	RTI Str
ALL	0.71	V-2	4	0	130	75	95
	1.5	V-2	3	0	130	75	95
	3.0	V-2	2	0	130	75	95
	6.0	V-2	2	0	130	75	95

Comparative Tracking Index (CTI): 9

Dielectric Strength (MV/mm): 13

High-Voltage Arc Tracking Rate (HVTR): 0

Dimensional Stability (%): -

Inclined Plane Tracking (IPPT): -

Volume Resistivity (10⁹ ohm-cm): 14

High Volt. Low Current Arc Resist (D485): 6

(f1) - Suitable for outdoor use with respect to exposure to ultraviolet light, water exposure and immersion in accordance with UL 746C.

NOTE - (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "Zytel" for Zytel or "BLEN" for Blended or "DEL" for Delrin or "CRA" for Grastin or "RYN" for Rynite or "ETPV" for ETPV grades.

r9 - Virgin and regrip up to 50% by weight inclusive, have the same basic material characteristics for ALL colors down to 0.71mm. For thickness 0.48mm to 0.76mm the same basic material characteristics exist with the exception of generic RTIs for all properties and Regrip exceeding 25% is limited to V-2 Flammability for WT, RD, BK.


AMBIAL G4 small-scale test data does not pertain to building materials, furnishings and related contents. AMBIAL G4 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product designs and applications, where the combustibility is determined by UL.

Report Date: 1996-07-29

Last Revised: 2010-07-27

© 2011 Underwriters Laboratories Inc.

CALUS

 康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.				TITLE LED間隔柱		產品規格圖面	
				MATERIAL NYLON 66 UL94V-2		DATE 2013.07.01	
				FINISH		DRAWN T.C	
				COLOR NATURAL		CHECK 	
PART NUMBER LEDSB-11		DRAWING NUMBER LEDSB-11		UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE		APPROVED 	
SIZE A4	SCALE 5:1	UNIT mm	REV A				