




CHASSIS HOLE: $\phi 3.5\text{mm}$
THICKNESS: 0.8~2.0mm



CABLE CLAMP



CABLE TIES

PART NO.	MATERIAL
SWPL-22V0	NYLON 66 UL94V-0
SWPL-22	NYLON 66 UL94V-2

NOTE: 1. SHRINKING IS NORMAL STATUS.

內縮為正常現象。

2. MADE OF EQUIVALENT MATERIAL.

均可使用同等材質。

3. THE COLOR BATCH TEST REPORT IS ONLY FOR FIRST LOT TEST.

色母環保檢測報告, 僅提供原始測試報告。



康揚企業股份有限公司
KANG YANG HARDWARE ENTERPRISE CO., LTD.
康揚塑膠(東莞)有限公司
KANG YANG PLASTIC(DONG GUAN)CO., LTD.
康哲電腦配件(吳江)有限公司
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE 2006.04.18	TITLE POWER CORD RETENTION CLAMP	DWG. NO. SWPL-22		PART NO. SEE ABOVE	
	DRAWN Pinda	MATERIAL SEE ABOVE	SIZE A4		SPEC. DWG.	
	CHECKED 林德翔	COLOR BLACK	FINISH		REV B	
	APPROVED Kang	UNLESS OTHERWISE SPECIFIED TOLERANCE: SEE ABOVE		SCALE: 3:2	UNIT mm	SHEET 1 OF 1