


DIM.	TOL
L≤10	±0.2
10<L≤30	±0.3
30<L≤50	±0.5
50<L≤100	±0.7
100<L≤250	±1.2
ABOVE 250	±1.5

REVISIONS			
REV	DESCRIPTION	DATE	BY



QMF22 Component - Plastics
E I DUPONT DE NEMOURS & CO INC
ENGINEERING POLYMERS CHESTNUT RUN PLAZA PO BOX 80713 WILMINGTON DE 19880

Wednesday, September 15, 2004

B41938

Material Designation: 101(+)(f), 101F(+)(f), 101L(+)(f), E101(+)(f), B101L(f), 132F(+)(f), 135F(+)(f)
Product Description: Polyamide 66 (PA66), designated "Zytel" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	0.71	V-2	4	0	130	75	85	725	960
	1.5	V-2	3	0	130	75	85	750	960
	3	V-2	2	0	130	75	85	800	960
	6	V-2	2	0	130	75	85	800	960

CTE: 0

HVTR: 0

D495; 6

IEC Ball Pressure (Ck):

Dielectric Strength (kV/mm): 13

Volume Resistivity (10¹⁰ohm-cm): 14

Dimensional Stability(%):

ISO Tensile Strength (MPa):

ISO Flexural Strength (MPa):

ISO Heat Deflection (°C):

ISO Tensile Impact (kJ/m²):

ISO Izod Impact (kJ/m²):

ISO Charpy Impact (kJ/m²):

(+) Virgin and regrid up to 50% by weight inclusive, have the same basic material characteristics.

(f) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

NOTE (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" or "MIN" or "ZEN" or "DEL" or "CRA" or "RYN".

Report Date: 7/29/1996

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

 康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.				TITLE		SPEC. DWG.	
				電線束線座		DATE	
				MATERIAL		2010.12.20	
				NYLON 66 UL94V-2		DRAWN	
PART NUMBER				FINISH		ROBERT	
THA-19				COLOR		CHECK	
DRAWING NUMBER				NATURAL			
THA-19				UNLESS OTHERWISE SPECIFIED TOLERANCE		APPROVED	
SIZE		SCALE		SEE ABOVE			
A4		2:1		UNIT			
		mm		REV			
				A			