




HOLE IN CHASSIS: $\phi 4\text{mm}$
CHASSIS THICKNESS: 1.0~1.6mm

PART NO.	COLOR	MAX BUNDLE DIA mm(inch)	MIN. LOOP TENSILE STRENGTH kgs(Lbs.)
GTP-130I	NATURAL	28(1.10")	13.6(30)
GTP-130I(B)	BLACK		

NOTE:1. SHRINKING IS NORMAL STATUS.

內縮為正常現象。

2. MADE OF EQUIVALENT MATERIAL.

均可使用同等材質。

3. THE COLOR BATCH TEST REPORT IS ONLY FOR FIRST LOT TEST.

色母環保檢測報告, 僅提供原始測試報告。



康揚企業股份有限公司
KANG YANG HARDWARE ENTERPRISE CO., LTD.
康揚塑膠(東莞)有限公司
KANG YANG PLASTIC(DONG GUAN)CO., LTD.
康哲電腦配件(吳江)有限公司
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO., LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE 2001.04.26	TITLE CABLE TIES	DWG. NO. GTP-130I		PART NO. SEE ABOVE	
	DRAWN S.J.C	MATERIAL NYLON 66 UL94V-2				
	CHECKED 	COLOR SEE ABOVE	FINISH	SIZE A4	SPEC. DWG.	REV B
	APPROVED 	UNLESS OTHERWISE SPECIFIED TOLERANCE: SEE ABOVE		SCALE: 1:1	UNIT mm	SHEET 1 OF 1