

|           |  |      |  |           |             |      |    |
|-----------|--|------|--|-----------|-------------|------|----|
| 成型尺寸      |  | 公差   |  | REVISIONS |             |      |    |
| L≤10      |  | ±0.2 |  | REV       | DESCRIPTION | DATE | BY |
| 10<L≤30   |  | ±0.3 |  |           |             |      |    |
| 30<L≤50   |  | ±0.5 |  |           |             |      |    |
| 50<L≤100  |  | ±0.7 |  |           |             |      |    |
| 100<L≤250 |  | ±1.2 |  |           |             |      |    |
| ABOVE 250 |  | ±1.5 |  |           |             |      |    |

MOUNTING HOLE:  $\phi 57.15\text{mm}$   
CHASSIS THICKNESS: 6.35mm

QMFZ2 Component - Plastics      Wednesday      E41938

E I DUPONT DE NEMOURS & CO INC  
ENGINEERING POLYMERS CHESTNUT RUN PLAZA PO BOX 80713 WILMINGTON DE 19880  
Material Designation: 101(+)(f1), 101F(+)(f1), 101L(+)(f1), B101(+)(f1), B101L(f1), 132F(+)(f1), 135F(+)(f1)  
Product Description: Polyamide 66 (PA66), designated "Zytel" furnished as pellets.

| Color | Min. Thick. (mm) | Flame Class | HAI | RTI Elec | RTI Imp | RTI Str | IEC GWIT | IEC GWFI |
|-------|------------------|-------------|-----|----------|---------|---------|----------|----------|
| ALL   | 0.71             | V-2         | 4   | 0        | 130     | 75      | 725      | 960      |
|       | 1.5              | V-2         | 3   | 0        | 130     | 75      | 750      | 960      |
|       | 3                | V-2         | 2   | 0        | 130     | 75      | 800      | 960      |
|       | 6                | V-2         | 2   | 0        | 130     | 75      | 800      | 960      |

CTI: 0      HVTR: 0      D495: 6      IEC Ball Pressure (C):  
Strength dV/mm: 13      Volume Resistivity (10<sup>10</sup>ohm-cm): 14      Dimensional Stability(%)  
Strength 0.05%      ISO Flexural Strength 0.05%      Deflection (C):  
ISO Tensile      ISO Charpy Impact (J/m<sup>2</sup>):  
Impact (J/m<sup>2</sup>):      ISO Izod Impact (J/m<sup>2</sup>):

(+) Virgin and reground up to 50% by weight inclusive, have the same basic material characteristics.  
(f1) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.  
NOTE (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" or "MIN" or "ZEN" or "DEL" or "CRA" or "RYN".  
Report Date: 7/29/1996      Underwriters Laboratories Inc®  
UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices a

|                                                                                                                                                                                                             |              |                           |          |                                                      |  |                    |  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---------------------------|----------|------------------------------------------------------|--|--------------------|--|
| <div><p>康揚企業股份有限公司<br/>KANG YANG HARDWARE ENTERPRISE CO., LTD.<br/>康揚塑膠(東莞)有限公司<br/>KANG YANG PLASTIC(DONG GUAN) CO., LTD.<br/>康哲電腦配件(吳江)有限公司<br/>KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.</p></div> |              |                           |          | TITLE<br>護線環                                         |  | 產品規格圖面             |  |
|                                                                                                                                                                                                             |              |                           |          | MATERIAL<br>NYLON 66 UL94V-2                         |  | DATE<br>2011.08.18 |  |
|                                                                                                                                                                                                             |              |                           |          | FINISH                                               |  | DRAWN<br>K.W       |  |
|                                                                                                                                                                                                             |              |                           |          | COLOR<br>BLACK                                       |  | CHECK<br>朱益建       |  |
| PART NUMBER<br>NB-4757                                                                                                                                                                                      |              | DRAWING NUMBER<br>NB-4757 |          | UNLESS OTHERWISE SPECIFIED<br>TOLERANCE<br>SEE ABOVE |  | APPROVED<br>Kang   |  |
| SIZE<br>A4                                                                                                                                                                                                  | SCALE<br>1:1 | UNIT<br>mm                | REV<br>A |                                                      |  |                    |  |