



成型尺寸	公差
L≤10	±0.2
10<L≤30	±0.3
30<L≤50	±0.5
50<L≤100	±0.7
100<L≤250	±1.2
ABOVE 250	±1.5

REVISIONS			
REV	DESCRIPTION	DATE	BY



QMFZ2 Component - Plastic
 NAN YA PLASTICS CORP
 PLASTICS 4TH DIV 3RD FL 201 TUNG HWA NORTH RD TAIPEI TAIWAN
 Material Designation: 1403G6

Friday, October 24, 2003

E130155

Product Description: Polybutylene Terephthalate (PBT), furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	0.75	V-0	3	0	130	130	140	-	-
	1.5	V-0	2	0	130	130	140	-	-
	3	V-0	2	0	130	130	140	-	-
CTI: 2		HVTR: 1		D495: 6		IEC Ball Pressure (C): -		Dimensional Stability(%) 0	
Dielectric Strength (kV/mm): 33		Volume Resistivity (10 ¹⁰ ohm-cm): 14		ISO Tensile Strength (MPa): -		ISO Flexural Strength (MPa): -		ISO Heat Deflection (C): -	
ISO Tensile Impact (kJ/m ²): -		ISO Izod Impact (kJ/m ²): -		ISO Charpy Impact (kJ/m ²): -					

Report Date: 1/11/1991

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

 <p>康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.</p>	TITLE 電晶體座		產品規格圖面	
	MATERIAL PBT UL94V-0+GF		DATE 2012.02.09	
	FINISH		DRAWN ROBERT	
	COLOR BLACK		CHECK 林秀卿 朱益霆	
PART NUMBER BGCV-15	DRAWING NUMBER BGCV-15		UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	
SIZE A4	SCALE 3:1	UNIT mm	REV A	APPROVED Kang