


成型尺寸	公差
L≤10	±0.2
10<L≤30	±0.3
30<L≤50	±0.5
50<L≤100	±0.7
100<L≤250	±1.2
ABOVE 250	±1.5

REVISIONS			
REV	DESCRIPTION	DATE	BY



註：內縮為正常現象。

QMFZ2 Component - Plastics  
 RHODIA ENGINEERING PLASTICS  
 QUARTIER BELLE-ETOILE AVE RAMBOZ BOITE POSTALE 64 69192 ST FONS CEDEX FRANCE  
 Material Designation: B 50H1(r1)  
 Product Description: Polyamide 66/6 (PA66/6), designated "Technyl" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	0.38	V-0	4	0	120	-	-	-	-
	0.75	V-0	4	0	120	90	95	-	-
BK	1	V-0, 5VB	4	0	120	90	95	-	-
	1.5	V-0	4	0	120	90	95	-	-
	3	V-0	3	0	120	90	95	-	-

CTI: 0 HVTR: 0 D495: 6 IEC Ball Pressure (Cr) -  
 Dielectric Strength (kV/mm) - Volume Resistivity (10<sup>9</sup>ohm-cm) - Dimensional Stability(%) -  
 ISO Tensile Strength (MPa) - ISO Flexural Strength (MPa) - ISO Heat Deflection (Cr) -  
 ISO Tensile Impact (kJ/m<sup>2</sup>) - ISO Izod Impact (kJ/m<sup>2</sup>) - ISO Charpy Impact (kJ/m<sup>2</sup>) -  
 (r1) Virgin and regrind up to 50% by weight incl. have the same basic material characteristics, except for the 5VB rating.

Report Date: 10/21/1993 Underwriters Laboratories Inc®  
 UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices a

 康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.	TITLE		電晶體座		產品規格圖面			
	MATERIAL		NYLON 66 UL94V-0		DATE		2012.02.02	
	FINISH				DRAWN		C. S. L	
	COLOR		NATURAL		CHECK		朱益建	
PART NUMBER		DRAWING NUMBER		UNLESS OTHERWISE SPECIFIED TOLERANCE		APPROVED		
TRGV-6.7V0		TRGV-6.7V0		SEE ABOVE		朱益建		
SIZE	SCALE	UNIT	REV					
A4	5:1	mm	A					