



REVISIONS			
REV	DESCRIPTION	DATE	BY




M3 X 0.5P  
(BRASS NUT X2)  
INSERT MOLDING

銅柱埋入射出  
EFFECTIVE FASTEN LENGTH: 7 mm  
有效牙深7mm

符合歐盟ROHS規範 (RoHS Compliant)	
★鉛Pb	<1000PPM
★鎘Cd	< 100PPM
★汞Hg	<1000PPM
★六價鉻Cr6+	<1000PPM
★多溴聯苯類PBBs	<1000PPM
★多溴聯苯醚類PBDEs	<1000PPM

NOTE: MADE OF EQUIVALENT MATERIAL.  
使用同等材質

 <p>康揚企業股份有限公司 KANG YANG HARDWARE ENTERPRISE CO., LTD. 康揚塑膠(東莞)有限公司 KANG YANG PLASTIC(DONG GUAN) CO., LTD. 康哲電腦配件(吳江)有限公司 KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.</p>				TITLE	THREADED SPACER	SPEC. DWG	
				MATERIAL	NYLON 66 UL94V-2	DATE	2015.05.12
				FINISH		DRAWN	LUKE
				COLOR	NATURAL	CHECK	
PART NUMBER	HPCA-21	DRAWING NUMBER	HPCA-H	UNLESS OTHERWISE SPECIFIED TOLERANCE	SEE ABOVE	APPROVED	
SIZE	A4	SCALE	2:1	UNIT	mm	REV	A