


DIM.	TOL
5mm DOWN	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm UP	±1.0

MOUNTING HOLE  $\phi 3$   
THICKNESS 1.2~2.0mm



MOUNTING HOLE  $\phi 3$   
THICKNESS 1.2~2.0mm

PART NO.	A
LCF-3	3.2
LCF-4	4.0
LCF-5	5.0
LCF-6S	6.0
LCF-6	6.35
LCF-8	8.0
LCF-9	9.5
LCF-10.6	10.6
LCF-11	11.2
LCF-12	12.0
LCF-14.4	14.4
LCF-15	15.0
LCF-16	16.0
LCF-17	17.0
LCF-20	20.2
LCF-22	22.0
LCF-25	25.4

NOTE: 1. SHRINKING IS NORMAL STATUS.

內縮為正常現象。

2. MADE OF EQUIVALENT MATERIAL.

均可使用同等材質。



康揚企業股份有限公司  
KANG YANG HARDWARE ENTERPRISE CO., LTD.  
康揚塑膠(東莞)有限公司  
KANG YANG PLASTIC(DONG GUAN)CO.,LTD.  
康哲電腦配件(吳江)有限公司  
KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED.  DO NOT SCALE DRAWING	DATE	1999.08.26	TITLE	SPACER SUPPORT		DWG. NO.	LCF-H		PART NO.	SEE ABOVE		
	DRAWN	JASON		MATERIAL	NYLON 66 UL94V-2							
	CHECKED	林祺翔		COLOR	NATURAL	FINISH			SIZE	A4		
	APPROVED	Kang		UNLESS OTHERWISE SPECIFIED TOLERANCE: SEE ABOVE			SCALE: 3:1	UNIT	mm	SPEC. DWG	REV	F
											SHEET 1 OF 1	