


RMM-XXX



RMM-3

PART NO.	L
RMM-57N	5.7
RMM-200N	20.0

MOUNTING HOLE: $\phi 6.5$
 MAX THICKNESS: 2.4mm

- NOTE: 1. SHRINKING IS NORMAL STATUS.
 內縮為正常現象。
 2. MADE OF EQUIVALENT MATERIAL.
 均可使用同等材質。
 3. RMM-XXX TO USE RMM-3 TO ASSEMBLE.
 RMM-XXX 與 RMM-3 搭配使用。



康揚企業股份有限公司
 KANG YANG HARDWARE ENTERPRISE CO., LTD.
 康揚塑膠(東莞)有限公司
 KANG YANG PLASTIC(DONG GUAN)CO.,LTD.
 康哲電腦配件(吳江)有限公司
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE	2002.06.11	TITLE	ROUND SPACER	DWG. NO.	RMM-3H	PART NO.	SEE ABOVE	
	DRAWN	S.J.C.	MATERIAL	NYLON 66 UL94V-2	SIZE	A4	SPEC. DWG.	REV	A
	CHECKED	李柏甯	COLOR	NATURAL	FINISH				
	APPROVED	<i>Kang</i>	UNLESS OTHERWISE SPECIFIED TOLERANCE:	SEE ABOVE	SCALE:	3:1	UNIT	mm	SHEET 1 OF 1