


DIM	TOL
5mm DOWN	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm UP	±1.0

REVISIONS			
REV	DESCRIPTION	DATE	BY



Component - Plastic

E41838

E I DUPONT DE NEMOURS & CO INC  
ENGINEERING POLYMERS, CHESTNUT RUN PLAZA, PO BOX 80713, WILMINGTON DE 19880  
101(r9)(f1), 101F(r8)(F1), 101L(r9)(f1), E101(r9)(f1), E101L(r9)(f1)  
Polyamide 66 (PA66), "Zytel", furnished as pellets

Color	Min Thick (mm)	Flame Class	HAI	HAF	RTI Elec	RTI Imp	RTI Str
ALL	0.71	V-2	4	0	130	75	85
	1.5	V-2	3	0	130	75	85
	3.0	V-2	2	0	130	75	85
	6.0	V-2	2	0	130	75	85

Comparative Tracking Index (CTI): 0  
Dielectric Strength (kV/mm): 13  
High-Voltage Arc Tracking Rate (SVTR): 0  
Dimensional Stability (%): -

Inclined Plane Tracking (IPT): -  
Volume Resistivity (10<sup>9</sup> ohm-cm): 14  
High Volt. Low Current Arc Resis (D485): 8

(F1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

NOTE: (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" for Zytel or "SH" for Nylon or "DEL" for Delrin or "GHA" for Gharlon or "RYN" for Rynite or "ETPV" for ETPV grades.

r9 - Virgin and ranging up to 50% by weight inclusive, have the same basic material characteristics for ALL colors down to 0.7mm. For thicknesses 0.40mm to 0.70mm the same basic material characteristics exist with the exception of generic RTI for all properties and Resist exceeding 28% is limited to V-2 Flammability for WT, RD, BK.

ANSI/UL 94 small-scale test data does not pertain to building materials, assemblies and related systems. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1995-07-29  
Last Revised: 2010-07-27

© 2011 Underwriters Laboratories Inc.



**康揚企業股份有限公司**  
KANG YANG HARDWARE ENTERPRISE CO., LTD.  
**康揚塑膠(東莞)有限公司**  
KANG YANG PLASTIC(DONG GUAN) CO., LTD.  
**康哲電腦配件(吳江)有限公司**  
KANG CHE COMPUTER COMPONENTS(WUJIANG) CO., LTD.

TITLE <b>LED SPACER SUPPORT</b>		SPEC. DWG.	
MATERIAL NYLON 66 UL94V-2		DATE	2001.10.11
FINISH		DRAWN	S.J.C.
COLOR NATURAL		CHECK	
PART NUMBER LEDI3-3	DRAWING NUMBER LEDI3-3	APPROVED	
SIZE A4	SCALE 4:1	UNIT mm	REV A
UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE		APPROVED <i>Kang</i>	